

INFINITY LUBE

**FUEL OX® INFINITY LUBE™
COOL-OX**
*PERFORMANCE OPTIMIZING A/C
& REFRIGERATION TREATMENT*

DESCRIPTION

Infinity Lube™ Cool-Ox reconditions, restores and maintains efficiency by improving heat transfer in condenser and evaporator coils in the air conditioning, heat pump and refrigeration systems. Cool-Ox is a metal conditioner and surface modifier that cleans and transitions metal surfaces into laminar surfaces with friction coefficients less than 0.1. This increase in lubricity makes A/C systems blow colder air and saves energy by having less run time. It is extremely important to note that Cool-Ox does not include elements of the halogen group such as chlorine, fluorine and sulfur that form highly corrosive acids like other competitors products. Cool-Ox does not contain PTFE (Teflon) or any other particulates like powdered metal or plastics. Cool-Ox has been thoroughly endorsed, tested and proven to be the only product of its kind. Whether you own a home or business this energy saving product is an absolute must and a tribute to American engineering.

APPLICATIONS

- HVAC/Air Conditioning (Residential & Commercial)
- Pre-Cooling & Manufacturing Processes
- Refrigeration storages, Transportation, & Distribution
- Automotive, Truck and Reefer A/C Systems

APPLICATION DIRECTIONS

One time treatment. Add one ounce to treat 1 ton of unit/rating.

PHYSICAL PROPERTIES

Concentrate Color.....Tan to Brown
Density.....7.8 lbs/gal (930 kg/m³)
Flash Point.....900°F (482°C)
Specific Gravity.....0.93
Chlorine.....NONE
Mineral Oil..... 0%



BENEFITS

- **Plant based & toxin free**
- **Reduces electrical energy caused by friction of the contacting points**
- **Reduces up to 30% or more on electrical bill. Amperage reductions of up to 50%**
- **Improves pool boiling & thermodynamics which delivers colder vent air faster**
- **Reduces equipment maintenance costs & compressor noises**
- **Extends equipment/cooling systems life**
- **Reestablishes lost system SEER (seasonal energy efficient ratio) performance**
- **Reduces oil fouling**
- **Improves lubrication in compressor**

AVAILABLE SIZES

3 fl oz (90m)
8 fl oz (240ml)
64 fl oz (1920ml)
55 US gallon drum (208 litre)

**BIOBASED & TOXIN FREE
MADE WITH PLANT BASED ESSENTIAL OILS**

THE INFORMATION IN THIS SHEET IS BELIEVED TO BE ACCURATE AT THE DATE OF ISSUE. BECAUSE CONDITIONS OF USE ARE BEYOND THE MANUFACTURER'S CONTROL NO GUARANTEE OR WARRANTY IS IMPLIED OR EXPRESSED
ISSUE DATE: 10/1/20